

PARQUET VARNISH UA



1L

5L

PRODUCT DESCRIPTION

Parquet Varnish UA is a one component solvent based polyurethane varnish. Parquet Varnish UA is designed to protect heavy used wooden floors such as commercial spaces. A hardener can be added to increase the chemical and mechanical resistance.

TECHNICAL DATA

DILUTION	WHITE SPIRIT
SOLID CONTENT	+/- 52% IN WEIGHT
VISCOSITY	+/- 150-200 SEC - DIN 4
GLOSS	MAT, SATIN AND GLOSSY

PREPARATION

The surface must be clean. If necessary, sand and degrease the wood.

USER INSTRUCTIONS

Apply the varnish with a brush or roller. It's recommended to apply 3 coats. Intermediate sanding between coats with grain 180. In order to obtain better results, a hardener can be added to the varnish (5%). Mix the harder with the varnish and let rest for 15 minutes. After mixing with the hardener, the pot life is +/- 4 hours. After-wards the product is unusable.

DRYING TIMES



Dust-free after +/- 1 hour
Recoatable after +/- 8 hours
Slightly chargeable after 24 hours

APPLYING QUANTITY



86-107 sq ft/ liter per coat

AFTER TREATMENT

Use Ciranova Hard floor fresh for regular maintenance. For periodic maintenance use Ciranova Hard Floor polish. For deep cleaning of a varnished floor and to remove old polish layers, use Ciranova Hard Floor Cleaner.

PRODUCT INFORMATION

Shelf Life: 1 year in original and well closed packaging.

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

Ciranova North-America

1255 22nd Street
San Francisco, CA 94107
tel. 415. 282. 2529 fax 415. 477. 2106
info@ciranova-na.com

www.ciranova-na.com